

# Hybrid

# Metropol 1500





100 Alabaster



Burnt Umber



300 Sable Oak



500 Cornsilk



Brass Oak



Apple-Box Gum



Marble Spotted Gum



Burl Oak



580 Fallow Oak



700 Platinum Grey



Pepper Oak



790 Silhouette Oak

While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice.

"Subject to proper installation, maintenance and local building code/regulatory approval.



## **Hybrid**

# Metropol 1500

Delivering super durable and impact resistant flooring with exquisite design, Metropol 1500 is a technologically advanced hybrid range that ticks all the right boxes. Available in a wide range of natural timber hues, your next project is a guaranteed winner with strong, stable and beautiful flooring that's easy to install.

### **Technical Data**

Type	Hybrid
Plank Thickness	6.5mm
Wear Layer	0.5mm
Dimensions	1500mm (L) x 228mm (W)
Planks per Box	6
M² per Box	2.05m <sup>2</sup>
M² per Pallet	123.12m²
Colours	12
Installation Method	Uniclic®

Finish	Matte
Surface	Embossed
Top Layer	Decorative Film & Wear Layer
Substrate Layer	Trigon® Core Technology (Limestone Composite)
Backing Layer	1.5mm IXPE
Profile	Micro Bevel
Protective Coating	PUR

#### **Performance**

					ISO23999		
Dimensional Stability	Length: 0.0 Width: 0.0	3 3 3					
	Curling 0.0						
Thermal Resistance	0.039m² K/w	0					
Thermal Conductivity	0.128 W/(m.K)						
Abrasion Rating	Group T						
	·						
Swelling After Submersion in Water	0.1%				ISO 24336		
Impact Sound Reduction	Test Application	Test Application					
	150mm Slab + 28mm Furring	150mm Slab + 28mm Furrings + 10mm Plasterboard					
	200m Slab	200m Slab					
	200mm Slab + 28mm Furring	200mm Slab + 28mm Furrings + 10mm Plasterboard					
	200mm Slab + R2.5 Insulation	47					
	250mm Slab + 28mm Furring	49					
Light Fastness	≥6	≥6					
Light Reflectance Values	100 Alabaster	46.14 %	180 Burnt Umber	8.60%	300 Sable Oak	18.44%	
	500 Cornsilk	30.04%	520 Brass Oak	22.30%	545 Apple-Box Gun	n 20.90%	
	555 Marble Spotted Gum	12.32%	560 Burl Oak	11.41%	580 Fallow Oak	15.47%	
	700 Platinum Grey	33.98%	720 Pepper Oak	19.10%	790 Silhouette Oak	13.31%	
Fire Classification	CRF 11.1kW/m <sup>2</sup>				ISO 9239		
	Smoke Value 210% minutes						
Slip Resistance	P3				AS/NZ 4586 - 2013		
Residential Warranty*	25 Year Hybrid Limited Residential Warranty						
Commercial Warranty <sup>†</sup>	10 Year Commercial Warranty available upon request						

#### Sustainability

Indoor Air Quality Green Building Council compliant for VOC emission rate limits











